

GRUNT NATUR

PROVIDES ANTISEPTIC TREATMENT FOR DIFFERENT SURFACES WITH BLEACH EFFECT IN AND OUTSIDE USE WITHOUT CHLORINE

PURPOSES

Grunt Natur is used for cleaning and protection against mould and rot; for general disinfection and antibacterial treatment. It bleaches the surface. The product is suitable for the application on different types of surfaces: plaster, concrete, putties, solid and non-solid mineral bases, fibrous cement boards, gypsum, gypsum plasterboards, bricks and other construction materials, as well as woodchip boards and wooden surfaces.

NB! Grunt Natur is not for the application on surfaces covered with varnish, paint, oil or other hygroscopic substances.

MAIN ADVANTAGES

- This is new generation product, it deeply penetrates the wood and has excellent fixation with the surface.
- Once absorbed, Grunt Natur creates a hydrophobic layer with antiseptic properties;
- The solution is intended for anti-bacterial treatment (tested according to EN 1276) and is used to clean mould and blue stains;
- Removes rot and unpleasant odours, bleaches, cleans dirty surfaces, protects the surface
- Combines chemically with material and reduces its porosity.
- Does not affect gluing and painting properties of wood;
- Wood remains durable and recoatable;
- Stops already started decay;
- Preserves the texture and doesn't prevent the ventilation of the wood;
- Ecologically safe, non-toxic, non-carcinogenic;
- Fire and explosion proof, does not contain VOC and chlorine;
- No colour or smell.

DIRECTIONS FOR USE

Before applying Grunt Natur, always clean the surface of all dust, bark or other contaminants. Grunt Natur may be applied with a brush or roller at the temperature above +5⁰C (with humidity under 75%). Apply 2 coats with an interval of 30–40 minutes with normalized total consumption being 100–250 g/m². Freshly applied agent should be dried at air temperature +12⁰C to +40⁰C (with humidity under 75%). Under these conditions, the drying time is 1-3 days, but climate conditions like low temperatures and/or high relative humidity can lengthen the drying time.

You can paint over or cover the treated surface with other finishing materials.

When using Grunt Natur to clean mineral bases and plate joints, impregnate the surface and let it function for 10 minutes, then scrub the surface with brush and wash it with water.

NB! Before treating a painted surface, test a small area first! If the product contacts accidentally with the painted surface, wash immediately with plenty of water!

Do not process frozen wood! Do not mix Grunt Natur with other products! Stir thoroughly before applying! (Bottom sediment doesn't affect the quality of the product).

STORAGE AND TRANSPORTATION

Store and transport Grunt Natur in hermetically sealed original containers separately from food products.

Keep at temperature above -5⁰C. The storing period of the product is 24 months.

COMPOSITION

Iron orthophosphate dihydrate, water and additives.

SAFETY MEASURES

Keep locked up and out of the reach of children. Do not get in eyes, on skin, or on clothing. Rinse thoroughly in case of contact with eyes or mouth. Get medical advice/attention if you feel unwell. Use only outdoors or in a well-ventilated area. Discard with other household waste products.